



Massachusetts
Institute of
Technology



Grossman Group of
Clean Energy

Computing Requirements for

Computational Design of Novel Energy Materials


Yun Liu, Jeffrey C. Grossman

Department of Materials Science and Engineering

Massachusetts Institute of Technology

NERSC BES Requirements for 2017
October 8-9, 2013
Gaithersburg, MD

Materials will shape the future of renewable energy



Solar PV





Biofuels



Batteries

Thermoelectrics






Hydrogen Storage



Solar Thermal



Example of a single element



Carbon



Carbon in energy to date



One Barrel of oil =
1.73 MWh of energy

Burning Carbon for energy



Same carbon, different use

Using 1% of carbon in the same 1 barrel to make plastic for thin-film solar cells.




One Barrel of oil =
16,000 MWh energy
(5% efficient, 1 year)




10,000 X more energy from same material!


Beyond burning: a carbon materials energy future




All-Carbon Solar Cells



Water desalination



Thermoelectrics



Solar thermal fuels

Summary of Projects in 2013



m655, Quantum simulation of nanoscale energy conversion

- Solar Cells Based on Monolayer Materials
- Energy alignment in Metal/Organic Interfaces and its effect on solar cell efficiency
- Thermal and electronic transport in patterned graphene for thermal electric applications


m1797, Design of high-efficiency solar thermal fuels via first-principles computations

- Optical properties and excited state dynamics of STF
- High-throughput search of novel STF materials


Two-Dimensional Monolayer Materials for Ultra-Thin Excitonic Solar Cells




Maximize Energy Efficiency in Solar Cells at Metal-Organic Interfaces



Chemically Functionalized Graphene for Thermoelectric Applications




Patterned 2D shapes on graphene reduces the room-temperature thermal conductivity.



Due to a combination of boundary and clamping effects.

High Throughput search of STF materials

Solar Thermal Fuel (STF)



Challenges:


- Increase stability
- Higher energy density
- Lower cost

High Throughput search

Screen through databases of molecules




Better STF candidates (2000 discovered)




Photoisomerization Dynamics for Solar Thermal Fuels

Excited-state forces in time-dependent density-functional theory

Excited state for trans-azobenzene



Excited state for cis-azobenzene



Access to dynamics of complicated systems (e.g. azobenzene + nanotube)



octopus

Future research topics (by 2017)

- Patterning and functionalization in 2D materials for solar cell.
- Functionalization of patterned graphene for thermal electric applications.
- Photophysics of STF with templates and functionalized groups.
- High-throughput (HT) design of STF materials with newly discovered design principles.

Computational Strategies

- We employed empirical MD, DFT, TDDFT, GW and Bethe-Salpeter equation calculations.
- The codes we use are LAMMPS, VASP, Gaussian, Octopus, Quantum-Espresso, and our own java-based HT code.
- Our biggest computational challenges are from simulations of large patterned structures with functionalization (>500 atoms).
- Our parallel scaling is mostly limited by parallelization efficiency of VASP on more than 2000 cores.
- We expect to use the same (or similar) set of codes by 2017. One of our group member (David Strubbe) is a developer of the Octopus code for TDDFT simulations.

Current HPC Usage

- We have 14M SUs in 2013, mostly running on Hopper
- Typical run on 100~1000 cores for 48 hours, around 2000 jobs a year.
- 2TB data read/written per run
- Typically use 2GB~4GB memory per core, 1.5T aggregate memory per run.
- Besides standard HPC services, we asked for code compilation assistance as well as optimization advice.
- We use 10TB scratch file system, 7TB shared file system and 7TB archival space except for the High Throughput simulations.
 - HT simulation alone can generate 10TB scratch file and 5TB data at a time.

HPC Requirements for 2017

- Around 100M SUs needed except HT simulations by 2017.
 - HT simulations along may take 100M SUs, depending on the configuration space explored.
- We expect to run concurrently on 1000~64000 cores for 48 hours per job. 2000 jobs per year.
- Data read/write will increase by a factor of 5 to 10TB as a result of increased system size except HT simulations.
 - HT simulations may generate 1PB scratch and 500TB data at a time.
- Memory per core will increase by a factor of 4 to 8GB/core considering increased parallelization. Aggregate memory usage per run will reach 50TB.
- We would like to ask for code compilation, database server support, web server host service from NERSC.

Summary

- With the expected improvements with NERSC, we will be able to design new energy materials which are currently beyond the simulation power.
- Our researches will be more CPU intensive than I/O intensive, with the exception of disk space. Therefore faster/more CPUs will best benefit our researches.
- With access to 32X your current NERSC allocation, we will for the first time be able to explore a full subset of configuration space with computational materials design.
- Result libraries generated from HT simulations would be of interest to the general materials research community, therefore additional webserver service will become useful by 2017.

Group and Support



U.S. DEPARTMENT OF
ENERGY



Advanced Research Projects Agency • ENERGY

